IDEAL®

Inter Connection Devices Bnc Connector Plugs For Industrial Power Socket And Coupler (connector)



ID-013-4 ID-023-4

Earth contact position		4h	
Rated current(A)		16	32
	Pole	3	
Dimension(mm)	a	122	139
	b	59	75
	c	51	64
	Φ	6	8
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :110-130V-2P+E
Protection degree: IP44



ID-013 ID-023

Earth contact position		6h	
Rated current(A)		16	32
	Pole	3	
Dimension(mm)	a	122	139
	b	59	75
	c	51	64
	Φ	6	8
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :220-240V-2P+E
Protection degree: IP44



ID-014 ID-024

[illegible]		[illegible]	
Rated current(A)		16	32
	Pole	4	
Dimension(mm)	a	122	139
	b	65	75
	c	55	64
	Φ	6	8
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :380-415V-3P+E
Protection degree: IP44



ID-015 ID-025

[illegible]		[illegible]	
Rated current(A)		16	32
	Pole	5	
Dimension(mm)	a	130	143
	b	72	84
	c	64	70
	Φ	8	8
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :220-380V~ 240-415V~ 3P+N+E
Protection degree: IP44



ID-033 ID-043

Earth contact position		6h	
Rated current(A)		63	125
	Pole	3	
Dimension(mm)	a	231.5	293
	b	110	125
	c	16-38	30-50
	Φ	110	125
Cable nominal cross-section area(mm²)		6-16	16-50

Current (A) :63A125A
Voltage (V) :220-240V-2P+E
Protection degree: IP67



ID-034 ID-044

[illegible]		[illegible]	
Rated current(A)		63	125
	Pole	4	
Dimension(mm)	a	231.5	293
	b	110	125
	c	16-38	30-50
	Φ	110	125
Cable nominal cross-section area(mm²)		6-16	16-50

Current (A) :63A.125A
Voltage (V) :380-415V-3P+E
Protection degree: IP67



ID-035 ID-045

[illegible]		[illegible]	
Rated current(A)		63	125
	Pole	5	
Dimension(mm)	a	231.5	293
	b	110	125
	c	16-38	30-50
	Φ	110	125
Cable nominal cross-section area(mm²)		6-16	16-50

Current (A) :63A.125A
Voltage (V) :220-380V~ 240-415V~ 3P+N+E
Protection degree: IP67



ID-013L-4 ID-023L-4

Earth contact position		4h	
Rated current(A)		16	32
	Pole	3	
Dimension(mm)	a	141	178
	b	59	75
	c	51	64
	Φ	8	10
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :110-130V-2P+E
Protection degree: IP44



ID-013L ID-023L

Earth contact position		6h	
Rated current(A)		16	32
	Pole	3	
Dimension(mm)	a	141	178
	b	59	75
	c	51	64
	Φ	8	10
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :220-240V-2P+E
Protection degree: IP44



ID-014L ID-024L

[illegible]		[illegible]	
Rated current(A)		16	32
	Pole	4	
Dimension(mm)	a	141	178
	b	59	75
	c	51	64
	Φ	8	10
Cable nominal cross-section area(mm²)		1-1.25	2.5-6

Current (A) :16A.32A
Voltage (V) :380-415V-3P+E
Protection degree: IP44



ID-015L ID-025L

[illegible]		[illegible]	
Rated current(A)		16	32
	Pole	5	
Dimension(mm)	a	169	181
	b	72	84
	c	64	70
	Φ	10	10
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :220-380V~ 240-415V~ 3P+N+E
Protection degree: IP44



ID-113-4 ID-123-4

Earth contact position		4h	
Rated current(A)		16	32
	Pole	3	
Dimension(mm)	a	135	153
	b	92	102
	c	71	71
	d	50	65
	e	57	57
	f	20	20
	g	32.5	32.5
	h	6.5	6.5
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :110-130V-2P+E
Protection degree: IP44



IDEAL®

Inter Connection Devices Bnc Connector Plugs For Industrial Power Socket And Coupler (connector)





ID-113 ID-123

Earth contact position		6h	
Rated current(A)		16	32
	Pole	3	
Dimension(mm)	a	135	153
	b	92	102
	c	71	71
	d	50	65
	e	57	57
	f	20	20
	g	32.5	32.5
	h	6.5	6.5
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :220-240V~2P+E
Protection degree: IP44





ID-114 ID-124

Earth contact position		6h	
Rated current(A)		16	32
	Pole	4	
Dimension(mm)	a	140	152
	b	95	104
	c	71	71
	d	56	64.5
	e	57	57
	f	20	20
	g	32.5	32.5
	h	6.5	6.5
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :380-415V~3P+E
Protection degree: IP44



ID-115 ID-125

Earth contact position		6h	
Rated current(A)		16	32
	Pole	5	
Dimension(mm)	a	139	153
	b	100	107
	c	71	71
	d	63	70
	e	57	57
	f	20	20
	g	32.5	32.5
	h	6.5	6.5
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :220-380V~ / 240-415V~ 3P+N+E
Protection degree: IP44



ID-133 ID-143

Earth contact position		6h	
Rated current(A)		63	125
	Pole	3	
Dimension(mm)	a	134	154
	b	311	338
	c	108	122
	d	111	130
	e	20	20
	f	153	185
	g	6	6.2
Cable nominal cross-section area(mm²)		6-25	25-70

Current (A) :63A.125A
Voltage (V) :220-240V~2P+E
Protection degree: IP67



ID-134 ID-144

Earth contact position		6h	
Rated current(A)		63	125
	Pole	4	
Dimension(mm)	a	134	154
	b	311	338
	c	108	122
	d	111	130
	e	20	20
	f	153	185
	g	6	6.2
Cable nominal cross-section area(mm²)		6-25	25-70

Current (A) :63A.125A
Voltage (V) :380-415V~3P+E
Protection degree: IP67



ID-135 ID-145

Earth contact position		6h	
Rated current(A)		63	125
	Pole	5	
Dimension(mm)	a	134	154
	b	311	338
	c	108	122
	d	111	130
	e	20	20
	f	153	185
	g	6	6.2
Cable nominal cross-section area(mm²)		6-25	25-70

Current (A) :63A.125A
Voltage (V) :220-380V~ / 240-415V~ 3P+N+E
Protection degree: IP67



ID-113L-4 ID-123L-4

Earth contact position		4h	
Rated current(A)		16	32
	Pole	3	
Dimension(mm)	a	168	190
	b	92	102
	c	71	71
	d	50	65
	e	57	57
	f	20	20
	g	32.5	32.5
	h	6.5	6.5
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :110-130V~2P+E
Protection degree: IP44



ID-113L ID-123L

Earth contact position		6h	
Rated current(A)		16	32
	Pole	3	
Dimension(mm)	a	168	190
	b	92	102
	c	71	71
	d	50	5
	e	57	57
	f	20	20
	g	32.5	3.5
	h	6.5	.5
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :220-240V~2P+E
Protection degree: IP44



ID-114L ID-124L

Earth contact position		6h	
Rated current(A)		16	32
	Pole	4	
Dimension(mm)	a	170	190
	b	95	104
	c	71	71
	d	56	64.5
	e	57	57
	f	20	20
	g	32.5	32.5
	h	6.5	6.5
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :380-415V~3P+E
Protection degree: IP44



ID-115L ID-125L

Earth contact position		6h	
Rated current(A)		16	32
	Pole	5	
Dimension(mm)	a	166	190
	b	100	107
	c	71	71
	d	63	70.5
	e	57	57
	f	20	20
	g	32.5	32.5
	h	6.5	6.5
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :220-380V~ / 240-415V~ 3P+N+E
Protection degree: IP44



ID-213-4 ID-223-4

Earth contact position		4h	
Rated current(A)		16	32
	Pole	3	
Dimension(mm)	a	131	150
	b	68	92
	c	50	65
	Φ	6	8
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :110-130V~2P+E
Protection degree: IP44



ID-213 ID-223

Earth contact position		6h	
Rated current(A)		16	32
	Pole	3	
Dimension(mm)	a	131	150
	b	68	92
	c	50	65
	Φ	6	8
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :220-240V~2P+E
Protection degree: IP44



IDEAL®

Inter Connection Devices Bnc Connector Plugs For Industrial Power Socket And Coupler (connector)

ID-214 ID-224

Earth contact position		6h	
Rated current(A)		16	32
	Pole	4	
Dimension(mm)	a	131	150
	b	79	92
	c	56	65
	Φ	6	8
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :380-415V-3P+E
Protection degree: IP44



ID-215 ID-225

Earth contact position		6h	
Rated current(A)		16	32
	Pole	5	
Dimension(mm)	a	139	154
	b	90	100
	c	63	70.5
	Φ	8	8
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :220-380V~ / 240-415V~ 3P+N+E
Protection degree: IP44



ID-233 ID-243

Earth contact position		6h	
Rated current(A)		63	125
	Pole	3	
Dimension(mm)	a	240	303
	b	115	128
	c	16-38	30-50
	Φ	108	120
Cable nominal cross-section area(mm²)		6-16	16-50

Current (A) :63A.125A
Voltage (V) :220-240V-2P+E
Protection degree: IP67



ID-234 ID-244

Earth contact position		6h	
Rated current(A)		63	125
	Pole	4	
Dimension(mm)	a	240	303
	b	115	128
	c	16-38	30-50
	Φ	108	120
Cable nominal cross-section area(mm²)		6-16	16-50

Current (A) :63A.125A
Voltage (V) :380-415V-3P+E
Protection degree: IP67



ID-235 ID-245

Earth contact position		6h	
Rated current(A)		63	125
	Pole	5	
Dimension(mm)	a	240	303
	b	115	128
	c	16-38	30-50
	Φ	108	120
Cable nominal cross-section area(mm²)		6-16	16-50

Current (A) :63A.125A
Voltage (V) :220-380V~ / 240-415V~ 3P+N+E
Protection degree: IP67



ID-213L-4 ID-223L-4

Earth contact position		4h	
Rated current(A)		16	32
	Pole	3	
Dimension(mm)	a	150	189
	b	68	92
	c	50	65
	Φ	8	10
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :110-130V-2P+E
Protection degree: IP44



ID-213L ID-223L

Earth contact position		6h	
Rated current(A)		16	32
	Pole	3	
Dimension(mm)	a	150	189
	b	68	92
	c	50	65
	Φ	8	10
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :220-240V-2P+E
Protection degree: IP44



ID-214L ID-224L

Earth contact position		6h	
Rated current(A)		16	32
	Pole	4	
Dimension(mm)	a	149	189
	b	79	92
	c	56	65
	Φ	8	10
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :380-415V-3P+E
Protection degree: IP44



ID-215L ID-225L

Earth contact position		6h	
Rated current(A)		16	32
	Pole	5	
Dimension(mm)	a	179	193
	b	90	100
	c	63	70.5
	Φ	8	10
Cable nominal cross-section area(mm²)		1-2.5	2.-6

Current (A) :16A.32A
Voltage (V) :220-380V~ / 240-415V~ 3P+N+E
Protection degree: IP44





ID-313-4 ID-323-4

Earth contact position		4h	
Rated current(A)		16	32
	Pole	3	
Dimension(mm)	a	74	91
	b	70	88
	c	70	70
	d	70	70
	e	56	56
	f	56.5	56.5
	g	56.5	56.5
	h	24	29
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :110-130V-2P+E
Protection degree: IP44



ID-313 ID-323

Earth contact position		6h	
Rated current(A)		16	32
	Pole	3	
Dimension(mm)	a	74	91
	b	70	88
	c	70	70
	d	70	70
	e	56	56
	f	56.5	56.5
	g	56.5	56.5
	h	24	29
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :220-240V-2P+E
Protection degree: IP44



ID-314 ID-324

Earth contact position		4h	
Rated current(A)		16	32
	Pole	4	
Dimension(mm)	a	76	90
	b	80	87
	c	70	70
	d	70	70
	e	56	56
	f	56.5	56.5
	g	56.5	56.5
	h	25	30
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :380-415V-3P+E
Protection degree: IP44



IDEAL®

Inter Connection Devices Bnc Connector Plugs For Industrial Power Socket And Coupler (connector)

ID-315 ID-325

Earth contact position	4h	
Rated current(A)	16	32
Pole	5	
Dimension(mm) a	76	93
b	86	95
c	70	70
d	70	70
e	56	56
f	56.5	56.5
g	56.5	56.5
h	26	28
Cable nominal cross-section area(mm²)	1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :220-380V~ 240-415V~ 3P+N+E
Protection degree: IP44



ID-333 ID-343

Earth contact position	6h	
Rated current(A)	63	125
Pole	3	
Dimension(mm) a	100	120
b	100	120
c	80	101
d	80	101
e	54.5	68
f	88	96
g	114	129
h	108	122
i	70	88
Cable nominal cross-section area(mm²)	6-25	25-70

Current (A) :63A.125A
Voltage (V) :220-240V~2P+E
Protection degree: IP67



ID-334 ID-344

Earth contact position	6h	
Rated current(A)	63	125
Pole	4	
Dimension(mm) a	100	120
b	100	120
c	80	101
d	80	101
e	54.5	68
f	88	96
g	114	129
h	108	122
i	70	88
Cable nominal cross-section area(mm²)	6-25	25-70

Current (A) :63A.125A
Voltage (V) :380-415V~3P+E
Protection degree: IP67



ID-335 ID-345

Earth contact position	6h	
Rated current(A)	63	125
Pole	5	
Dimension(mm) a	100	120
b	100	120
c	80	101
d	80	101
e	54.5	68
f	88	96
g	114	129
h	108	122
i	70	88
Cable nominal cross-section area(mm²)	6-25	25-70

Current (A) :63A.125A
Voltage (V) :220-380V~ 240-415V~ 3P+N+E
Protection degree: IP67



ID-413-4 ID-423-4

Earth contact position	4h	
Rated current(A)	16	32
Pole	3	
Dimension(mm) a	76	86
b	70.5	99
c	63	80
d	49	62
e	49	72
f	49	70.5
g	49	62
h	10.5	13
i	37	40
	70	90
Cable nominal cross-section area(mm²)	1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :110-220V-2P+E
Protection degree: IP44



ID-413 ID-423

Earth contact position	6h	
Rated current(A)	16	32
Pole	3	
Dimension(mm) a	76	86
b	70.5	99
c	63	80
d	49	62
e	49	72
f	49	70.5
g	49	62
h	10.5	13
i	37	40
	70	90
Cable nominal cross-section area(mm²)	1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :220-240V~2P+E
Protection degree: IP44



ID-414 ID-424

Earth contact position	4h	
Rated current(A)	16	32
Pole	4	
Dimension(mm) a	80	100
b	86	97
c	75	80
d	59	68
e	66	80
f	61	70.5
g	60	59.5
h	13	13
i	46	55
	85	96
Cable nominal cross-section area(mm²)	1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :380-415V~3P+E
Protection degree: IP44



ID-415 ID-425

Earth contact position	4h	
Rated current(A)	16	32
Pole	5	
Dimension(mm) a	80	97
b	86	97
c	75	81.5
d	64	80.5
e	74	85
f	61	70.5
g	60	60.5
h	13	13.5
i	43	53
	88	96.5
Cable nominal cross-section area(mm²)	1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :220-380V~ 240-415V~ 3P+N+E
Protection degree: IP44



ID-513-4 ID-523-4

Earth contact position	6h	
Rated current(A)	16	32
Pole	3	
Dimension(mm) a	134	148
b	80	88
c	71	71
d	43.5	57.5
e	57	57
f	20	20
g	32.5	32.5
h	6.5	6.5
Cable nominal cross-section area(mm²)	1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :110-130V-2P+E
Protection degree: IP44



ID-513 ID-523

Earth contact position	6h	
Rated current(A)	16	32
Pole	3	
Dimension(mm) a	134	148
b	80	88
c	71	71
d	43.5	57.5
e	57	57
f	20	20
g	32.5	32.5
h	6.5	6.5
Cable nominal cross-section area(mm²)	1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :220-240V~2P+E
Protection degree: IP44



ID-514 ID-524

Earth contact position	4h	
Rated current(A)	16	32
Pole	4	
Dimension(mm) a	139	148.5
b	80	88
c	71	71
d	50	57
e	57	57
f	20	20
g	32.5	32.5
h	6.5	6.5
Cable nominal cross-section area(mm²)	1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :380-415V~3P+E
Protection degree: IP44



ID-515 ID-525

Earth contact position	4h	
Rated current(A)	16	32
Pole	5	
Dimension(mm) a	138.5	150.5
b	83	90
c	71	71
d	55	64
e	57	57
f	20	20
g	32.5	33.5
h	6.5	6.5
Cable nominal cross-section area(mm²)	1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :220-380V~ 240-415V~ 3P+N+E
Protection degree: IP44



IDEAL®

Inter Connection Devices Bnc Connector Plugs For Industrial Power Socket And Coupler (connector)

ID-533 ID-543

Earth contact position		6h	
Rated current(A)		63	125
Pole		3	
Dimension(mm)	a	193	220
	b	122	140
	c	153	185
	d	109	130
	e	19	17
	f	6	8
	g	288	330
	h	127	140
	PG	29	36
Cable nominal cross-section area(mm²)		6-16	16-50

/Current (A) :63A.125A
/Voltage (V) :220-240V~2P+E
/Protection degree: IP67



ID-534 ID-544

Earth contact position		6h	
Rated current(A)		63	125
Pole		4	
Dimension(mm)	a	193	220
	b	122	140
	c	153	185
	d	109	130
	e	19	17
	f	6	8
	g	288	330
	h	127	140
	PG	29	36
Cable nominal cross-section area(mm²)		6-16	16-50

Current (A) :63A.125A
Voltage (V) :380-415V~3P+E
Protection degree: IP67



ID-535 ID-545

Earth contact position		6h	
Rated current(A)		16	32
Pole		5	
Dimension(mm)	a	193	220
	b	122	140
	c	153	185
	d	109	130
	e	19	17
	f	6	8
	g	288	330
	h	127	140
	PG	29	36
Cable nominal cross-section area(mm²)		6-16	16-50

Current (A) :63A.125A
Voltage (V) :220-380V~ / 240-415V~ 3P+N+E
Protection degree: IP67





ID-613-4 ID-623-4

Earth contact position		4h	
Rated current(A)		16	32
Pole		3	
Dimension(mm)	a	56	56
	b	56	56
	c	70.5	70.5
	d	70.5	70.5
	e	45	57
	f	23	28
	g	42	51
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :110-130V~2P+E
Protection degree: IP44



ID-613 ID-623

Earth contact position		6h	
Rated current(A)		16	32
Pole		3	
Dimension(mm)	a	56	56
	b	56	56
	c	70.5	70.5
	d	70.5	70.5
	e	45	57
	f	23	28
	g	42	51
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :220-240V~2P+E
Protection degree: IP44



ID-614 ID-624

Earth contact position		6h	
Rated current(A)		16	32
Pole		4	
Dimension(mm)	a	56	56
	b	56	56
	c	70.5	70.5
	d	70.5	70.5
	e	45	57
	f	23	28
	g	42	51
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :380-415~3P+E
Protection degree: IP44



ID-615 ID-625

Earth contact position		6h	
Rated current(A)		16	32
Pole		5	
Dimension(mm)	a	56	56
	b	56	56
	c	70.5	70.5
	d	70.5	70.5
	e	57	63
	f	23	28
	g	42	51
Cable nominal cross-section area(mm²)		1-2.5	2.5-6

Current (A) :16A.32A
Voltage (V) :220-380V~ / 240-415V~ 3P+N+E
Protection degree: IP44



IDI-633 ID-643

Earth contact position		6h	
Rated current(A)		63	125
Pole		3	
Dimension(mm)	a	100	120
	b	81	100
	c	20	22
	d	108	105
	e	109	124
	f	75	100
	g	6.5	6.5
Cable nominal cross-section area(mm²)		6-16	16-50

Current (A) :63A.125A
Voltage (V) :220-240V~2P+E
Protection degree: IP67



ID-634 ID-644

Earth contact position		6h	
Rated current(A)		63	125
Pole		4	
Dimension(mm)	a	100	120
	b	81	100
	c	20	22
	d	108	102
	e	109	124
	f	75	100
	g	6.5	6.5
Cable nominal cross-section area(mm²)		6-16	16-50

Current (A) :63A.125A
Voltage (V) :380-415V~3P+E
Protection degree: IP67



ID-635 ID-645

Earth contact position		6h	
Rated current(A)		63	125
Pole		5	
Dimension(mm)	a	100	120
	b	81	100
	c	20	22
	d	108	102
	e	109	124
	f	75	100
	g	6.5	6.5
Cable nominal cross-section area(mm²)		6-16	16-50

Current (A) :63A.125A
Voltage (V) :220-380V~ / 240-415V~ 3P+N+E
Protection degree: IP67



ID-012

Dimension(mm)	a	104
	b	42
	c	5
Cable nominal cross-section area(mm²)		1-2.5

Current (A) :16A
Voltage (V) :220-240V~
Protection degree: IP44



ID-212

Dimension(mm)	a	131
	b	57
	c	5
	D	48
Cable nominal cross-section area(mm²)		1-2.5

Current (A) :16A
Voltage (V) :220-240V~
Protection degree: IP44



IDEAL®

Hew Generation Quick Interconnection Devices Ben Connector Plugs For Industrial Power,Socket And Coupler(Connector)

Code:
QJ-1012-4
Input:
1 plug 16A 110V 2P+E
出/Output:
2 Connector 16A 110V 2P+E
Protection Degree:
IP44
Color:Yellow

Code:
QJN-013/023
Nominal Current (A):
16A
Input:
1 plug 220V 2P+E
Output:
1 Connector 220V 2P+E
Protection Degree:
IP44

Code:
QJ-1012
Input:
1 plug 16A 220V 2P+E
Output:
2 Connector 16A 220V 2P+E
Protection Degree:
IP44
Color:Blue

Code:
QJ-8213
Nominal Current (A):
16A
Voltage (V):
220-240V~
No.poles:2P+E
Protection Degree:
IP44

Code:
QJ-1012/4
Input:
1 plug 16A 380V 3P+E
Output:
2 Connector 16A 380V 3P+E
Protection Degree:
IP44
Color:Red

Code:
QJ-10132
Nominal Current (A):
16A
Input:
1 plug 220V 2P+E
Output:
3 Connector 220V 2P+E
Protection Degree:
IP67

Code:
QJ-1013-4 QJ-1023-4
Input:
1 plug 16A(32) 110V 2P+E
Output:
3 Connector 16A(32) 110V 2P+E
Protection Degree:
IP44
Color:Yellow

Code:
I0132/0132
Nominal Current (A):
16A
Input:
1 plug 220V 2P+E
Output:
3 Connector 220V 2P+E
Protection Degree:
IP67

Code:
QJ-1013 QJ-1023
Input:
1 plug 16A(32) 220V 2P+E
Output:
3 Connector 16A(32) 220V 2P+E
Protection Degree:
IP44
Color:Blue

Code:
QJ-1605
Nominal Current (A):
16A
Input:
1 plug 415V 3P+N+E
Output:
2 Sockets 16A
220-240V 1P+N
Protection Degree:
IP56

Code:
QJ-1014 QJ-1024
Input:
1 plug 16A(32) 380V 3P+E
Output:
3 Connector 16A(32) 380V 3P+E
Protection Degree:
IP44
Color:Red

Code:
QJ-1605A
Nominal Current (A):
16A
Input:
1 plug 415V 3P+N+E
Output:
1 Socket 16A 220V 2P+E
Protection Degree:
IP44

Box Size:
280x220x125mm
QJ-313 1只
QJ-315 1只
DZ47:2P 16A 1只
DZ47:4P 16A 1只

Box Size:
430x140x95mm
QJ-413 2只
QJ-112 2只
DZ47:2P 16A 1只
DZ47:2P 32A 2只

Box Size:
167x120x108mm
Nominal Current(A):
16A
32A
Voltage (V):
380-415V~
No.poles:3P+E
Protection Degree:
Ip44
With switch and interlock

Box Size:
400x140x95mm
QJN-4132 3
DZ47:2P 16A 1
DZ47:1P 16A 2

Box Size:
167x120x108mm
Nominal Current(A):
16A
32A
Voltage (V):
220-380V~
240-415V~
No.poles:3P+N+E
Protection Degree:
IP44
With switch and interlock

Box Size:
430x140x95mm
QJ-313 3
DZ47:2P 16A 1
DZ47:1P 16A 2

Box Size:
167x120x108mm
Nominal Current(A):
16A
32A
Voltage (V):
220-380V~
240-415V~
No.poles:3P+N+E
Protection Degree:
With switch and interlock

Box Size:
430x140x95mm
QJ-3152 3
DZ47:4P 50A 1

Box Size:
430x140x95mm
QJ-112 6
DZ47:2P 32A 2

Box Size:
430x140x95mm
QJ-413 3
DZ47:1P 16A 1
1P 40A

Box Size:
430x140x95mm
QJ-413 3
QJN-013 1
DZ47:2P 16A 1
DZ47:1P 16A 2

Box Size:
445x85x110mm
QJN-3152 3
DZ47:4P 63A 1

IDEAL®